

CLAIMS

1. An electromagnetic transponder of the type including a parallel oscillating circuit adapted to being excited by a series oscillating circuit of a read/write terminal when the transponder enters the field of the terminal, wherein the components of the oscillating circuit of the transponder are sized so that the coupling coefficient between the respective oscillating circuits of the terminal and of the transponder rapidly decreases when the distance separating the transponder from the terminal becomes smaller than a predetermined value.

2. The electromagnetic transponder of claim 1, wherein said value is 5.cm.

3. The electromagnetic transponder of claim 1, wherein an inductance of the parallel oscillating circuit is minimized.

4. The electromagnetic transponder of claim 1, wherein an inductance of the parallel oscillating circuit is chosen in accordance with the following relation:

$$k_{opt} = \sqrt{\frac{R_1 L_2}{R_2 L_1}},$$

where  $k_{opt}$  represents the coupling coefficient providing a maximum voltage across the parallel oscillating circuit, where  $R_1$  represents the series resistance of the series oscillating circuit, where  $R_2$  represents the equivalent resistance of the transponder brought in parallel on inductance  $L_2$ , and where  $L_1$  represents the inductance of the series oscillating circuit.

5. The electromagnetic transponder of claim 1, having an oscillating circuit wherein the components are sized based on an operating point at a median distance of a desired operating range, chosen to correspond to a coupling coefficient as close as possible to an optimal coupling coefficient in accordance with the following relation:

$$V_{2max}(k_{opt}) = \sqrt{\frac{R_2}{R_1}} \frac{V_g}{2},$$

where  $V_{2max}$  is the voltage across the parallel oscillating circuit for the optimal coupling between the oscillating circuits,  $R_1$  is the series resistance of the series oscillating circuit,  $R_2$  is the equivalent resistance of the transponder brought in parallel on its oscillating circuit, and  $V_g$  is the excitation voltage of the series oscillating circuit.

5

6. The electromagnetic transponder of claim 1, wherein the number of turns of the inductance of its oscillating circuit is smaller than 3.

7. The electromagnetic transponder of claim 1, wherein the respective values of the capacitance and of the inductance of the parallel oscillating circuit range between 20 and 500 pf and between 0.1 and 10  $\mu$ H.

8. A terminal for generating an electromagnetic field adapted to cooperating with at least one transponder when said transponder enters this field, including a series oscillating circuit for generating the electromagnetic field, this series oscillating circuit being sized so that the coupling coefficient between the respective oscillating circuits of the terminal and of the transponder strongly decreases when the distance separating the transponder from the terminal becomes smaller than a predetermined value.

9. The terminal of claim 8, wherein the components of its oscillating circuit are sized to fulfill the operating conditions of the transponder of claim 1.

10. The terminal of claim 9, wherein the inductance of its series oscillating circuit includes between 3 and 15 turns.

25

11. A system of contactless electromagnetic transmission between a terminal and a transponder, wherein the transponder is that of claim 1.

12. A system of contactless electromagnetic transmission between a terminal and a transponder, wherein the terminal is that of claim 8.

30

Sub  
C1  
add  
B1